

# CDB200 TRIAXIAL FIBERGLASS



## Material Technical Data Sheet

### Material Description:

STITCHING	POLYESTER 75/D YARD
STITCH WEIGHT	.25oz/yd <sup>2</sup>
FIBER TYPE	E-GLASS
AREAL WIEGHT	781 g/m <sup>2</sup> (23.04oz/yd <sup>2</sup> )
COMPATABILITY	POLYESTER/EPOXY/VINYLESTER
WIDTH	50 INCHES

### Material Construction:

<b>PLY</b>	<b>0° DEGREE</b>
FIBER SPECIFICATIONS	DIRECT ROVING
FIBER TEX	900 TEX
WEIGHT	354 g/m <sup>2</sup> (10.44oz/yd <sup>2</sup> )
WIDTH	50 INCHES

<b>PLY</b>	<b>+45° DEGREE</b>
FIBER SPECIFICATIONS	DIRECT ROVING
FIBER TEX	300 TEX
WEIGHT	200 g/m <sup>2</sup> (5.90oz/yd <sup>2</sup> )
WIDTH	50 INCHES

<b>PLY</b>	<b>90° DEGREE</b>
FIBER SPECIFICATIONS	DIRECT ROVING
FIBER TEX	300 TEX
WEIGHT	17 g/m <sup>2</sup> (.50oz/yd <sup>2</sup> )
WIDTH	50 INCHES

<b>PLY</b>	<b>-45° DEGREE</b>
FIBER SPECIFICATIONS	DIRECT ROVING
FIBER TEX	300 TEX
WEIGHT	200 g/m <sup>2</sup> (5.90oz/yd <sup>2</sup> )
WIDTH	50 INCHES

The information herein is general information designed to assist customers in determining whether Orca products are suitable to their applications. Orca products are intended for sale to industrial and commercial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents and suitability for their specific applications. **Nothing herein constitute any warranty express or implied, including any warranty of merchantability or fitness for a particular purpose**, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.